

NG to LPG CONVERSION for the S600GR

Conversion only to be carried out by a qualified person.

- 1/ Turn OFF and Disconnect any Gas or Electrical connection safely.
- 2/ Remove all the screws from the back cover and hold onto the screws.

Main Burner jet.

- 3/ To remove the main burner jet, disconnect the ¼” gas line, and remove the two screws holding the main gas aluminum burner holder.
- 4/ Replace the jet with the 0.8mm jet supplied.
- 5/ Refit in reverse all components, items 3 and 4.

Griller Burner jet.

- 6/ Remove the screws around the grill cover and hold on to the screws.
- 7/ To remove the griller jet disconnect the ¼” gas line, remove the screw from the aeration shroud and hold on to the screw.
- 8/ Replace the griller jet with the 0.96mm jet supplied.
- 9/ Refit in reverse all components, items 7 and 8.
- 10/ Remove the NG label and fit the LPG label supplied in the same location.
- 11/ Do not use the NG regulator supplied for LPG connection.

Fan Speed resistor replacement.

- 12/ Remove the 68 ohm / 10 watt ceramic resistor from the terminal block and fit a 100 ohm / 10 watt resistor supplied in the conversion kit.

Refit the back cover and secure with the screws in step 2.

Reconnect the gas and electricity supply accordingly and test the oven.

Hold onto NG jets, 68 ohm resistor and regulator for future use.

If you have any concerns with this conversion please contact the Glen Dimplex Australia Customer Care Line 1300 556 816.

2/205 Abbots Road Dandenong South Victoria 3175.